

## 4 Order data - X20CP158x <https://www.jd-rep.com/english/kontakt.html>



Contact  
 Jörg Dapkus  
 Mobile: +49 160 849 72 83

Order number	Short description
	<b>X20 PLC</b>
X20CP1583	X20 CPU, Atom 333 MHz (compatible), 128 MB DDR2 RAM, 1 MB SRAM, removable application memory: CompactFlash, 1 insert slot for X20 interface modules, 2 USB interfaces, 1 RS232 interface, 1 Ethernet interface 10/100/1000BASE-T, 1 POWERLINK interface, including power supply module, 1x terminal block X20TB12, slot cover and X20 end cover plate X20AC0SR1 (right) included, order application memory separately!
X20CP1584	X20 CPU, Atom 0.6 GHz, 256 MB DDR2 RAM, 1 MB SRAM, removable application memory: CompactFlash, 1 insert slot for X20 interface modules, 2 USB interfaces, 1 RS232 interface, 1 Ethernet interface 10/100/1000BASE-T, 1 POWERLINK interface, including power supply module, 1x terminal block X20TB12, slot cover and X20 end cover plate X20AC0SR1 (right) included, order application memory separately!
X20cCP1584	X20 CPU, coated, Atom 0.6 GHz, 256 MB DDR2 RAM, 1 MB SRAM, removable application memory: CompactFlash, 1 insert slot for X20 interface modules, 2 USB interfaces, 1 RS232 interface, 1 Ethernet interface 10/100/1000BASE-T, 1 POWERLINK interface, including power supply module, 1x terminal block X20TB12, slot cover and X20 end cover plate X20AC0SR1 (right) included, order application memory separately!
X20CP1585	X20 CPU, Atom 1.0 GHz, 256 MB DDR2 RAM, 1 MB SRAM, removable application memory: CompactFlash, 1 insert slot for X20 interface modules, 2 USB interfaces, 1 RS232 interface, 1 Ethernet interface 10/100/1000BASE-T, 1 POWERLINK interface, including power supply module, 1x terminal block X20TB12, slot cover and X20 end cover plate X20AC0SR1 (right) included, order application memory separately!
X20CP1586	X20 CPU, Atom 1.6 GHz, 512 MB DDR2 RAM, 1 MB SRAM, removable application memory: CompactFlash, 1 insert slot for X20 interface modules, 2 USB interfaces, 1 RS232 interface, 1 Ethernet interface 10/100/1000BASE-T, 1 POWERLINK interface, including power supply module, 1x terminal block X20TB12, slot cover and X20 end cover plate X20AC0SR1 (right) included, order application memory separately!
X20cCP1586	X20 CPU, coated, Atom 1.6 GHz, 512 MB DDR2 RAM, 1 MB SRAM, removable application memory: CompactFlash, 1 insert slot for X20 interface modules, 2 USB interfaces, 1 RS232 interface, 1 Ethernet interface 10/100/1000BASE-T, 1 POWERLINK interface, including power supply module, 1x terminal block X20TB12, slot cover and X20 end cover plate X20AC0SR1 (right) included, order application memory separately!
	<b>Required accessories</b>
	<b>CompactFlash cards</b>
0CFCRD.016GE.02	CompactFlash 16 GB extended temp.
0CFCRD.0512E.02	CompactFlash 512 MB extended temp.
0CFCRD.1024E.02	CompactFlash 1024 MB extended temp.
0CFCRD.2048E.02	CompactFlash 2048 MB extended temp.
0CFCRD.4096E.02	CompactFlash 4096 MB extended temp.
0CFCRD.8192E.02	CompactFlash 8 GB extended temp.
	<b>Included in delivery</b>
	<b>Batteries</b>
4A0006.00-000	Lithium battery, 3 V / 950 mAh, button cell
	<b>Locking plate</b>
X20AC0SR1	X20 locking plate, right
	<b>Terminal blocks</b>
X20TB12	X20 terminal block, 12-pin, 24 VDC keyed
	<b>Optional accessories</b>
	<b>Batteries</b>
0AC201.91	Lithium batteries 4 pcs., 3 V / 950 mAh button cell

Table 1: X20CP1583, X20CP1584, X20cCP1584, X20CP1585, X20CP1586, X20cCP1586 - Order data

### Included in delivery

Order number	Short description
4A0006.00-000	Backup battery (see also "Battery" on page 18)
-	Interface module slot covers
X20AC0SR1	X20 end cover plate (right)
X20TB12	X20 terminal block, 12-pin, 24 V coding

Table 2: X20 CPUs - Content of delivery