## 6 Order data - X20CP358x https://www.jd-rep.com/english/kontakt.html

	m	
	0.04 040	
E.	1.1	

Contact Jörg Dapkus Mobile: +49 160 849 72 83

Order number	Short description	
	X20 PLC	
X20CP3583	X20 CPU, Atom 333 MHz (compatible), 128 MB DDR2 RAM, 1 MB SRAM, removable application memory: CompactFlash, 3 insert slots for X20 interface modules, 2 USB interfaces, 1 RS232 interface, 1 Ethernet interface 10/100/1000BASE-T, 1 POWERLINK interface, including power supply module, 1x terminal block X20TB12, slot covers and X20 end cover plate X20AC0SR1 (right) included, order application memory separately!	
X20CP3584	X20 CPU, Atom 0.6 GHz, 256 MB DDR2 RAM, 1 MB SRAM, removable application memory: CompactFlash, 3 insert slots for X20 interface modules, 2 USB interfaces, 1 RS232 interface, 1 Ethernet interface 10/100/1000BASE-T, 1 POWERLINK interface, including power supply mod- ule, 1x terminal block X20TB12, slot covers and X20 end cover plate X20AC0SR1 (right) includ- ed, order application memory separately!	
X20cCP3584	X20 CPU, coated, Atom 0.6 GHz, 256 MB DDR2 RAM, 1 MB SRAM, removable application memory: CompactFlash, 1 insert slot for X20 interface modules, 2 USB interfaces, 1 RS232 interface, 1 Ethernet interface 10/100/1000BASE-T, 1 POWERLINK interface, including power supply module, 1x terminal block X20TB12, slot cover and X20 end cover plate X20AC0SR1 (right) included, order application memory separately!	
X20CP3585	X20 CPU, Atom 1.0 GHz, 256 MB DDR2 RAM, 1 MB SRAM, removable application memory: CompactFlash, 3 insert slots for X20 interface modules, 2 USB interfaces, 1 RS232 interface, 1 Ethernet interface 10/100/1000BASE-T, 1 POWERLINK interface, including power supply mod- ule, 1x terminal block X20TB12, slot covers and X20 end cover plate X20AC0SR1 (right) includ- ed, order application memory separately!	
X20CP3586	X20 CPU, Atom 1.6 GHz, 512 MB DDR2 RAM, 1 MB SRAM, removable application memory: CompactFlash, 3 insert slots for X20 interface modules, 2 USB interfaces, 1 RS232 interface, 1 Ethernet interface 10/100/1000BASE-T, 1 POWERLINK interface, including power supply mod- ule, 1x terminal block X20TB12, slot covers and X20 end cover plate X20AC0SR1 (right) includ- ed, order application memory separately!	
X20cCP3586	X20 CPU, coated, Atom 1.6 GHz, 512 MB DDR2 RAM, 1 MB SRAM, removable application memory: CompactFlash, 1 insert slot for X20 interface modules, 2 USB interfaces, 1 RS232 interface, 1 Ethernet interface 10/100/100BASE-T, 1 POWERLINK interface, including power supply module, 1x terminal block X20TB12, slot cover and X20 end cover plate X20AC0SR1 (right) included, order application memory separately!	
	Required accessories	
	CompactFlash cards	
0CFCRD.016GE.02	CompactFlash 16 GB extended temp.	
0CFCRD.0512E.02	CompactFlash 512 MB extended temp.	
0CFCRD.1024E.02	CompactFlash 1024 MB extended temp.	
0CFCRD.2048E.02	CompactFlash 2048 MB extended temp.	
0CFCRD.4096E.02	CompactFlash 4096 MB extended temp.	
0CFCRD.8192E.02	CompactFlash 8 GB extended temp.	
	Included in delivery	
	Batteries	
4A0006.00-000	Lithium battery, 3 V / 950 mAh, button cell	
	Locking plate	
X20AC0SR1	X20 locking plate, right	
	Terminal blocks	
X20TB12	X20 terminal block, 12-pin, 24 VDC keyed	
	Optional accessories	
	Batteries	
0AC201.91	Lithium batteries 4 pcs., 3 V / 950 mAh button cell	

Table 4: X20CP3583, X20CP3584, X20cCP3584, X20CP3585, X20CP3586, X20cCP3586 - Order data

## Included in delivery

Order number	Short description
4A0006.00-000	Backup battery (see also "Battery" on page 18)
-	Interface module slot covers
X20AC0SR1	X20 end cover plate (right)
X20TB12	X20 terminal block, 12-pin, 24 V coding

Table 5: X20 CPUs - Content of delivery